

US-1206

Lámpara COB "NOVA 10K" con Wireless Lamp



Fuente luz - Light source	High efficiency COB LED
Lumen - Luminous flux	1000-10000
Illuminance, lux@0,5 m	16000
Adjustable light output	5 levels
CRI	Ra> 80
CCT	6000K
Protection class	IP67/IK07
Cable	5m/3x1mm ² H05RN-F
Charging voltage current DC	100-240V
Power consumption	Max 84 W
Temperature	-10° to +40°C
Dimensions	302x102x298mm
• Peso neto - Net weight	4 Kg



US-1208

Lámpara COB LED "NOVA R" Lamp



Fuente luz - Light source	High efficiency COB LED
Lumen - Luminous flux	150-1500
Illuminance, lux@0,5 m	200-2000
Adjustable light output	5 levels
CRI	Ra> 80
CCT	6000K
Operating time	Up to 10 h
Charging time	3,5 h
Battery	3,6V/6000 mAh Li-on
Protection class	IP67/IK07
Impact resistance	1 m
Cable	1m USB
Charging voltage current DC	5V / 2A
Power consumption	Max 16,5 W
Temperature	-10° to +40°C
Dimensions	163x63x163 mm
• Peso neto - Net weight	0,705 Kg



US-1025

**Juego 2 tubos portátiles de leds especial para elevadores de turismos
2 Portable leds tubes special for automotive lifts set**

Este sistema de iluminación nos permite una fácil instalación, posibilidad de ampliar la instalación (1 transformador cada 2 tubos fluorescentes, y lo más importante que gracias al sistema de leds nos reduce de forma considerable el consumo eléctrico

This lighting system allows an easy installation with possibility to apply the installation (1 transformer for eachs 2 fluorescent, and the most important, thanks to the Leds system the electricity consumption reduces considerably)



Opcional - Optional

**US-1025/1
Soporte magnético para US-1025
Magnetic holder for US-1025**

Soporte imantado para sujeción de tubos fluorescente de forma rápida y sin necesidad de taladrar las plataformas
Magnetic holder system allows fitting the fluorescent in an easily way and without need to drill any platform



Fuente luz - Light source	2 x 156 SMD LED
Lumen - Luminous flux	2 x 1000
Illuminance, lux@0,5 m	2 x 1600
Adjustable light output	-
Beam angle	75°
CRI	Ra> 80
CCT	6000K
Protection class	IP67/IK07
Impact resistance	1 m
Cable	8m/H03VV-F 2x0,5 mm ²
Charging voltage current DC	24 V
Power consumption	Max 2x15 W
Temperature	-10° to +40°C
Dimensions	2 x Ø25 x 1234 mm
Peso neto - Net weight	2,1 Kg

